








SCHEDA TECNICA - TROMBONE

SUPPORTO PER TROMBONE BASSO

DM – S 12 H



	<p>DM-S12H-1 <i>Descrizione: Componente inferiore del supporto</i> <i>Dimensioni: 55,00 mm – diametro 16,00 mm</i> <i>Peso: 47,2 gr</i> Forature: Canale passante traversino di diametro 12,00 mm Foro passante per innesto asta di diametro 5,00 mm Fori per viti filettati M 4,00 mm</p>
	<p>DM-S12H-2 <i>Descrizione: Componente superiore del supporto</i> <i>Dimensioni: 40,00 mm – diametro 16,00 mm</i> <i>Peso: 23,2 gr</i> Forature: Canale passante traversino di diametro 12,00 mm Fori passanti di diametro 4,00 mm</p>
	<p>DM-S12H-3 <i>Descrizione: Asta sagomata per sostegno piastra</i> <i>Dimensioni: 85,00 mm * 55,00 mm – diametro 5,00 mm</i> <i>Peso: 20,00 gr</i></p>

	<p>DM-S12H-4 <i>Descrizione: Piastra sagomata per l'appoggio del dorso della mano (rivestimento interno con spugna)</i> <i>Dimensioni: 80 * 25 * 16 mm – spessore 2,00 mm</i> <i>Peso: 81,70 gr</i></p>
	<p>DM-S12H-5 <i>Descrizione: Viti per serraggio del supporto per trombone</i> <i>Dimensioni: lunghezza 14 mm * M 4,00 mm (filettatura)</i> <i>Peso: 5,00 gr</i></p>
	<p>DM-S125-6 <i>Descrizione: Aste sagomate del supporto con manico in legno</i> <i>Dimensioni: 80,00 mm – diametro 5,00 mm</i> <i>Peso per n°2 aste: 26,00 gr</i></p>
	<p>DM-S12H-7 <i>Descrizione: Manico in faggio inciso "DmBrass"</i> <i>Dimensioni: diametro 10 mm - lunghezza 4 cm</i> <i>Peso: 2 gr</i></p>

Il peso del supporto completo è di circa 180 grammi.

NB. La versatilità del supporto lo rende adattabile ad ogni modello di Trombone.

Materiali utilizzati

- Ottone e successivamente cromato per il corpo del supporto;
- Acciaio Inox per l'asta sagomata, piastra di appoggio e viti di fissaggio;
- Spugna espansa per l'interno della piastra di appoggio.



Dmbrass-Accessori Artigianali



dmbrass_accessoriartigianali

e-mail: info@dmbrass.com

www.dmbrass.com








DATA SHEET - TROMBONE

SUPPORT FOR BASS TROMBONE

DM – S 12 H



	<p>DM-S12H-1</p> <p><i>Description: Lower part of the support</i></p> <p><i>Dimensions: 55.00 mm (2.16 inch) - diameter 16.00 mm (0.63 inch)</i></p> <p><i>Weight: 47.2 gr</i></p> <p>Drilling: 12.00 mm (0.47 inch) diameter crossbar through channel</p> <p><i>Pass-through hole for rod coupling with a diameter of 5.00 mm (0.196 inch)</i></p> <p><i>Holes for threaded screws M 4.00 mm (0.157 inch)</i></p>
	<p>DM-S12H-2</p> <p><i>Description: Upper part of the support</i></p> <p><i>Dimensions: 40.00 mm (1.57 inch) - diameter 16.00 mm (0.63 inch)</i></p> <p><i>Weight: 23.2 gr</i></p> <p>Drilling: 12.00 mm (0.47 inch) diameter crossbar through channel</p> <p><i>4.00 mm (0.157 inch) diameter through holes</i></p>
	<p>DM-S12H-3</p> <p><i>Description: Shaped rod for plate support</i></p> <p><i>Dimensions: 85.00 mm * 55.00 mm (3.346 * 2.165 inch)</i></p> <p><i>diameter 5.00mm (0.196 inch)</i></p> <p><i>Weight: 20.00 gr</i></p>

	<p>DM-S12H-4</p> <p><i>Description: Shaped plate to support the back of the hand (internal lining with sponge)</i></p> <p><i>Size: 80 * 25 * 16mm (3.15 * 0.98 * 0.63 inch) thickness 2.00mm (0.079 inch)</i></p> <p><i>Weight: 81.70 gr</i></p>
	<p>DM-S12H-5</p> <p><i>Description: Screws for tightening the trombone support</i></p> <p><i>Size: Length 14mm * M 4.00mm (Thread – 0.157 inch)</i></p> <p><i>Weight: 5.00 gr</i></p>
	<p>DM-S12H-6</p> <p><i>Description: Shaped support rods with wooden handle</i></p> <p><i>Dimensions: 80.00 mm (3.15 inch) - diameter 5.00 mm (0.196 inch)</i></p> <p><i>Weight for 2 rods: 26.00 gr</i></p>
	<p>DM-S12H-7</p> <p><i>Description: "DmBrass" engraved beech handle</i></p> <p><i>Dimensions: Diameter 10 mm (0.39 inch) - length 4 cm (1.57 inch)</i></p> <p><i>Weight: 2 gr</i></p>

The weight of the complete support is approximately 180 grams.

NB. The versatility of the support makes it adaptable to any Trombone model.

Used materials

- Brass and subsequently chromed for the body of the support;
- Stainless steel for the shaped rod, support plate and fixing screws;
- Expanded sponge for the inside of the support plate.